

HIGH PRESSURE WATER BLASTERS



CEX20



Stainless steel pump-head.
Integrated unloader valve.



EEEx electrical box with main
switch, star delta starter &
overload relay.



Earth Cable with Clamp.



Balanced lifting eye for crane.



Stainless steel frame with built
in brake and solid wheels.



CEX20 Series
- ATEX compliant EEx equipped Units for Zone II use.

Model:	CEX20-200	CEX20-280	CEX20-350	CEX20-500
Technical details:				
60Hz Version				
W.P.: Bar/ Psi	170 / 2500	250 / 3600	350 / 5075	500 / 7250
Flow Lpm / Gpm	45 / 11.8	32 / 8.4	23 / 6	16 / 4.2
50Hz Version				
W.P.: Bar / Psi	200 / 2900	280 / 4060	350 / 5075	500 / 7250
Flow Lpm / Gpm	38 / 10	26 / 6.8	18 / 4.7	16 / 4.2
Electrical Spec.				
Motor Hp/ Kw	20 / 15	20 / 15	20 / 15	20 / 15
Voltage 60/50Hz	440 / 400	440 / 400	440 / 400	440 / 400
Amperage A	28 / 26	28 / 26	28 / 26	28 / 26
Dimensions (L x W x H): 1085 x 500 x 1080mm				
Weight: 255Kgs				

All models are CE marked & ATEX Approved.

Standard accessories incl. with each machine:

- 30m 4 core oil resistant electrical cable.
- 20m 500bar high pressure hose
c/w 1/2" stainless steel female swivel.
- Trigger operated dry shut gun
c/w 80cm stainless steel lance.
- Harden stainless steel straight jet spraying nozzle.
- Service Video

Optional accessories for each model:

- 20m 500bar high pressure hose
c/w 1/2" stainless steel female swivel. (Extension hose).
- Rotating nozzle.
- Short lance.
- Safety gear.
- Spare part kit.

www.denjet.com



SAFETY GEAR (PPE)



Single jet Rotating Nozzle










Blasting- Rotating Nozzle



Surface - Rotating Nozzle
500bar



CA12-250 Air Powered Blaster
Atex compliant Atex II cat.2G&D T5

	<p>Safety helmet c/w net visor and ear muff. Safety glasses are recommended to wear as well. Helmet: EN397. Net Visor: EN 1731:2006. Ear muff: EN 352-3:2002</p> <p>Part Number: 81600601</p>
	<p>Waterproof glove with protection for up to 500 bar pressure. The glove has a rough, sand patterned surface and the material itself provides lots of friction, all for the best grip on the tools. Supplied with separate inner glove in nylon for good comfort. Part Number: 81600669</p>
	<p>Water jetting boot for up to 800 bar (11600 psi) will protect the foot and the lower part of leg against water jet penetration.</p> <p>Available in size 42-46.</p>
	<p>Safety Apron - the full area of the Apron has built-in protection up to 500 bar (7250 psi). Ideal to wear in warm environments. The position of the Apron can be changed with the adjustable neckband. The Apron comes in one size. Weight 0.7 kg / 1.5 lbs.</p> <p>Part Number: 81600665</p>
	<p>Safety jacket and trousers with built-in protection up to 500 bar (7250 psi) in most areas. Thoughtful details such as openable ventilation in the armpit, comfortable cuffs, adjustable hood, elastic waist line and various pockets.</p> <p>Jacket 1.6kg - Trousers 1.3kg</p> <p>Available in size Medium, Large and X-large.</p>
	<p>Waterproof overall protect the operator only from spray, cold and flying debris. It does NOT deflect from direct jet impact. 190g PU/polyester - EN343 waterproof</p> <p>Size L - Part Number: 81600632 Size XL - Part Number: 81600609</p>
	<p>Hose protection. The gun is held near vital parts of the body the hose protection prevents injuries due to hose failure. Protects up to 500 bar (7250psi). The adjustable strap holds the hose protection securely in place.</p> <p>Length 750mm – weight 0.2kg.</p> <p>Part Number: 81600686</p> <p>Other safety gear available upon request.</p>



CEX40 Series

- ATEX compliant EEx equipped Units for Zone II use.

DEN-JET Marine Pte Ltd. 67A Joo Koon Circle, Singapore 629081.
Tel: +65 6268 1238 - Fax: +65 6268 2270 Email: denjetmarine@denjet.com
www.denjet.com



TST1310725